

Saint-Gobain API BV  
Newtonweg 1  
3846 BJ Harderwijk  
The Netherlands

P.O. Box 1  
3840 AA Harderwijk  
The Netherlands  
T +31 (0)341 474600  
F +31 (0)341 474626  
E sales@api.nl  
www.api.nl

Chamber of Commerce  
08015950  
BTW NL004318894.B.01

## Declaration of Performance 0007-190E

### Quick-Lock Accessories

1. Unique identification of product: Quick-Lock®
2. Identification of the construction product components:  
Cross tee clip TS, Wall bracket for Quick-Lock 24/60, Standard connector, Wall spring for Gyptone panels, Connector U-38, Connecting finger universal, Special hook finger, Connecting-clip use with T-profile/ Omega profile, Quick-Lock splice for QL 15/24-38, Holddown clips, Panel clip demountable, Panel clip not demountable, Panel clip for impact resistant systems, Twist clip with hanger ring for QL24, Card hanger for QL24, Wall spring, Cross-tee connection piece.
3. Intended use: Suspended ceiling substructure component for use internally in buildings.
4. Manufacturer: Saint-Gobain API BV Newtonweg 1 Harderwijk The Netherlands  
[www.api.nl](http://www.api.nl)
5. Authorized representatives: n.a.
6. System of assessment and verification of performance:
  - 6.1. N.a.
  - 6.2. Reaction to fire: Coil-coated steel system 3, Galvanized steel system 4
  - 6.3. Durability: System 4
7. Harmonized standard covering the construction product: EN 13964: 2014 suspended ceilings:
  - 7.1. N.a.
  - 7.2. Reaction to fire: Galvanized steel Commission decision 96/603/EC; Coil-coated steel Commission decision 2010/737/EC: Tests carried out by NB 0679 CSTB RA08-0251,
  - 7.3. Durability: EN 13964 Table 8
8. European Technical Assessment: n.a.

# QUICK-LOCK®

## Ceiling systems

### 9. Declared performances:

	7.1 Load bearing capacity			7.2 Reaction to fire	7.3 Durability
	Normal service load N	Ultimate load N	Notified body		
Cross tee clip TS	n.a.	n.a.	n.a.	Class A1	Class B
Wall bracket for Quick-Lock 24/60	n.a.	n.a.	n.a.	Class A1	Class B
Standard connector	n.a.	n.a.	n.a.	Class A1	Class B
Wall spring for Gyptone panels	n.a.	n.a.	n.a.	Class A1	Class B
Connector U-38	n.a.	n.a.	n.a.	Class A1	Class B
Connecting finger universal	n.a.	n.a.	n.a.	Class A1	Class B
Special hook finger	n.a.	n.a.	n.a.	Class A1	Class B
Connecting-clip use with T-profile/ Omega profile	n.a.	n.a.	n.a.	Class A1	Class B
Quick-Lock splice for QL 15/24-38	n.a.	n.a.	n.a.	Class A1	Class B
Holddown clips	n.a.	n.a.	n.a.	Class A1	Class B
Panel clip demountable	n.a.	n.a.	n.a.	Class A1	Class B
Panel clip not demountable	n.a.	n.a.	n.a.	Class A1	Class B
Panel clip for impact resistant systems	n.a.	n.a.	n.a.	Class A1	Class B
Twist clip with hanger ring for QL24	n.a.	n.a.	n.a.	Class A1	Class B
Card hanger for QL24	n.a.	n.a.	n.a.	Class A1	Class B
Wall spring	n.a.	n.a.	n.a.	Class A1	Class B
Cross-tee connection piece	n.a.	n.a.	n.a.	Class A1	Class B

Tolerances and dimensions fulfil the requirements as specified in EN 13964 table 2.

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performances point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for on behalf of the manufacturer:



Per-Erik Velin  
 Managing Director  
 Harderwijk NL 01-06-2020